



FOCUS TOUCH P10 Inform, inspire and interact

The Focus P10 is a multifunctional large format touch display suitable for every company. For your presentation, video conference or meeting, the P10 gives you a professional look and creates more attention to your message. Make your briefing simple and effective.

The precise touch operation offers optimal user convenience and the build in speakers, camera and microphone remove the need for any peripheral devices. The elegant Focus Touch is essential in every workspace. Add value to your business.

FOCUS TOUCH P10



For Focus on your presentations





2 x 30 Watt internal speakers



10 finger registration





Internal camera and microphone



Precise touch screen operation



2 year full exchange guarantee

P10 HEIGHT ADJUSTMENT UNIT



This electric height adjustment stand is an robust and stylish support for the display. The Focus P10 can be set to the right height easily and safely using the remote control. Including casters enable you to move the entire unit in an instant.

P10 MOUNTING SOLUTIONS



We offer a suitable assembly system for the Focus P10 for any room. For wall or floor solutions. Electrically or manually operated. Ask for the possibilities.

P10 CABINET



Professional protective cabinet with folding and lockable doors. Suitable for all Focus P10 display sizes: 55", 70" and 82". The cabinet is furnished with a high-quality enamelled surface and finished with aluminum profiles. The cabinet is writable on both sides, dry erasable and magnetic.

P10 WING SET



Whiteboard unit with folding wings.
Writable, dry erasable and magnetic.
Suitable for all display sizes. When closed the wings offers protection to the Focus Touch display. The wings are printable with text and images.

P10 MULTI CONNECT



Easily project your files directly from your notebook, smartphone or tablet onto the Focus P10 using optional hard- or software. With the possibility of simultaneous use by multiple persons.

FOCUS KIOSK



The Focus Kiosk is an interactive information unit with an integrated full HD touch display, PC and speakers. This modern and robust unit is prepared with wifi and easily potable by its casters. Available in all colors, matching your interior or company colors. Your logo can be added on the front.

Panel	55"	70"	82"	
Display Type	a-Si TFT active matrix (LED)			
Max. Resolution		1920 x 1080 Full HD		
Active Display Size	1209.6(H) x 680.4 (V)	1549.44(H) x 871.56(V)	1805.76(H) x 1015.74(V)	
Display Colors	16.7M (8Bit)			
Brightness	450cd/m2 (Typ.)	400 cd/m2 (Typ.)	450cd/m2 (Typ.)	
Contrast Ratio	4000 (Typ.)	4000 (Typ.)	5000 (Typ.)	
Viewing Angle	89°/ 89°/ 89°/ 89°(L/R/U/D)			
Response Time	8mS			
Refresh rate	60Hz			
Glass	Tempered AG 5mm			
Panel	Samsung PID-Pro panel			

Terminals	55"	70"	82"		
HDMI Input	Yes (2 port)				
Display port Input		Yes (1 port)			
RGB Input		Yes (D-Sub15-pin 1 port)			
Audio Input		Yes (3.5mm Stereo jack 1 port)			
Internal Speaker	Yes (2 x 30 W)				
Ext. Audio Output	Yes (3.5mm Stereo jack 1 port)				
Ext. SPDIF output (optical)	Yes (SPDIF 1 port)				
CVBS Input	Yes (VIDEO + Audio L/R 1 port)				
Component Input	Yes (1port)				
USB port	Yes (2 port): 1 Port : A Type Firmware Upgrade & Multimedia Player, 1 Port B Type Touch & Camera				
RS232	Yes				
Microphone output	Yes (3.5mm Stereo jack 1 port)				

Touchscreen	55"	70"	82"	
Touch Method		IR-Pro		
Max. number of touch		10		
Touch Method	Finger, gloved hand or any other pointer. Stylus minimum diameter 10 mm			
Calibration	Requires no software			
Interface	USB 2.0 (full speed), HID compliant, plug-and-play compatible			
Operating systems	Windows 7, Windows 8			

General	55"	70"	82"
Weight	53 kg	85 kg	108 kg
VESA	600 x 400 mm	800 x 400 mm	600 x 600 mm
Power Supply	AC 100V ~ 240V, 50/60Hz		
Power Consumption	240 Watt	290 Watt	400 Watt
ST-BY Power Consumption	0.5 Watt Under		
Dimension Set (WxHxD)	1283.9 x 753.9 x 105.0 mm	1634.3 x 955.9 x 105.0 mm	1891.3 x 1097.7 x 105.0 mm
Wall Mount Bracket	Option		
Mini PC Backpack	Option		

Environment	55"	70"	82"
Operating Temperature	50°F ~ 104°F (10°C ~ 40°C)		
Operating Humidity	10% ~ 80%, non-condensing		
Storage Temperature	-13°F ~ 140°F (-25°C ~ 60°C)		
Storage Humidity	5% ~ 95%, non-condensing		

Audio	55"	70"	82"
Picture Mode	Dynamic / Standard / Mild / User		
Picture Size	Auto / 4:3 / 16:9		
Back Light Control	0~100		
Surround	Surround / SRS TruSurround / Off		
Sound mode	Standard / Music / Movie / Sports / User		
Equalizer	120Hz / 500Hz / 1.5KHz / 10KHz		
Auto Volume	On / Off		

Others	55"	70"	82"
OSD Language	Densk, Deutsch, English, Espanol, Francais, Hrvatski, Italiano, Magyar, Nederlands, Norsk, Polski, Portugues, Romnete, Slovenina, Srpski, Suomi, Svenska, Slovak, Chinese,		
Menu Duration	Off / 5 sec / 10 sec / 15 sec		
PC Adjust	Auto Adjust / HV Position / Phase / Frequency		
Timer	On / Off timer		

Your Premium Partner: