

NEC M403W

Order Code: 60003978

NEC Professional Desktop Projector





The excellent price performance ratio makes this projector especially suitable for classrooms and mid sized meeting rooms. The filter free design with dust-protected DLP light engine, very long lamp life and low power consumption results into remarkably low cost of ownership. Various innovative new ECO functions such as the Ambient Light Sensor help to significantly reduce power consumption.

The optional DisplayNote Presenter licence adds the possibility for interactive, mobile presentation with tablets.

BENEFITS

Connect and share - with up to 40 wireless devices with the NEC Image Express Utility (Windows & MAC) as well as Wireless Image Utility (iOS & Android) software.

Maximum flexibility - due to large 1.7x optical zoom, horizontal and vertical keystone correction.

Robust and dust resistant - thanks to sealed DLP light engine.

Low cost of ownership - up to 8000h lamp life, low power consumption.

Great connectivity - due to numerous analog and digital connection terminals as well as network capability.



This document is © 2015 NEC Display Solutions Europe GmbH

NEC M403W - Technical Specification

Note::::::::::::::::::::::::::::::::::::		Decidation Technology	1 akin DI DW Taakaalaan
Appendix Signer 500 Appendix Signer ADDA Six Look Specific Xis Signer Xis Africa Machine Appendix Xis Xis Signer Xis	IMAGE	Projection Technology	1-chip DLP [™] Technology
Final Solution 00041 Final Solution 00041 Structure (Structure) Final Solution 0005 Con SOL Solution Final Solution 0005 Con SOL Solution Final Solution +20 Structure) Final Solutin			
Biglional 600401Lamb (part) 7056 for Mode) Lip (Lip (lip (Lip (Lip (Lip (Lip (Lip (Lip (Lip (L			
Line 200/01/02/02 Consol: Line 200/01/02 Consol: Line 2-2-31.5 Particle Particle 22-31.5 Particle P			
Imp (ib) 6005 /r 500 /r 600 /r 6			
Insi 12.2.4.2.16.7107402.000 Nepstein Argeh [1] 13.6.11.6 Payetin Argeh [1] 13.6.11.6 Payetin Argeh [1] 13.7.10.1 Serrer Sire (Sanga)[1] 12.7.20.1 Serrer Sire (Sanga)[1] 12.7.20.1 Serrer Sire (Sanga)[1] 12.7.20.7.7.7.20.007 Serrer Sire (Sanga)[1] 12.5.2.0.0000000000000000000000000000000			
speece creation >> 16 manual creation (manual vertical Pergeton factor Pergeton factor Pergeton Pergeton factor Pergeton factor Pergeton Pergeton factor Pergeton Pergeton factor Pergeton Pergeton factor Pergeton Pe			
Pajerion Acyp[1] 05-17. Pajerion Nature [n] 0.11-13.0 Screet Sci (Banch) [n] 0.11-13.0 Screet Sci (Banch) [n] 0.11-13.0 Screet Sci (Banch) [n] 0.11-13.0 Focus Ajalantet Maail Recard Sci (Banch) [n] 0.11-13.0 Screet Sci (Banch) [n] Maail Recard Sjalantet Maail Screet Sci (Banch) [n] Maail Recard Sjalantet Maail Screet Sci (Banch) [n] Screet Sci (Banch) [n] Screet Sci (Banch) [n] Scree			
Pageston Pristano Infrid 2 - 2 - 2 - 1 Pogeston Distano Infrid 26 - 12.36 Series Sin (Edganophilic) (Edg) 26 / 7.47 - 7.67 / 207 Zamin Marania Bagested Beschares 260 / 7.67 / 7.67 / 207 Damin Marania Bagested Beschares 260 / 100 /			
Peoplementational (m) NP = 16.0 Sames Same (singrad) (m) (m) Tax / 227 - 757 / 207 Com Manual Sames Same (singrad) (m) (m) Manual Sames Same (singrad) (m) (m) Manual Sames Same (singrad) (m) (m) Manual Sames Same (singrad) (m) (m) (m) (m) (m) (m) (m) (m) (m) (m		, , , , , , , , , , , , , , , , , , , ,	
Serie Sociespand [eq.] (Jene] 12.2017-2020 Can Manar Socies Adjustment Manar Socies Adjustmen			
Zeno Manual Facis Multiment Manual Exect Multiment Table 1 100 / 10000 / 1000 / 10000 / 10000 / 10000 / 10000 / 10000 / 10000 / 10000 / 10000 / 10000 / 10000 / 10000 / 100			
Focus Adjustment. Monod Supported Resolutions Supported Resolutions Monod Not Match (Min			
Supported Resolution Dip 1 (Dip 1) (Di			Manual
NUMBER 1: NO 1: 105 (XMA); 105 1: 105 (XMA); 105 1: 780 (XMA); 128 1: 102 NAXANAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA		Focus Adjustment	
RBB (inclug) Intel 1 × Min Dab E processmellable to component (YPEP) Dept 1 × RFA Input 2 × FAMI*" (Deep Dabs, Lis grand) Yelso Input 2 × FAMI*" (Deep Dabs, Lis grand) Madio Oppet 1 × RFA Madio Uppet 1 × RFA Madio 1 × PDA Madio Uppet 1 × RFA Madio 1 × PDA Madio Uppet 1 × RFA Madio 1 × PDA Madio Madio Madio Madio <td rowspan="2"></td> <td></td> <td>(WXGA+); 1400 x 1050 (SXGA+); 1366 x 768 (WXGA); 1360 x 768 (WXGA); 1280 x 1024 (Maximum resolution of digital input); 1280 x 1024 (SXGA); 1280 x 1024 (MAC 23"); 1280 x 960 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 1152 x 870 (MAC 21"); 1152 x 864 (XGA); 1024 x 768 (XGA); 832 x 624 (MAC 16"); 800 x 600 (SVGA); 720 x 576 SDTV 480p/480i; 720 x 576 (DVD progressive); 720 x 480 SDTV 576p/576i; 720 x 480 (SDTV 480p); 640 x 480 (VGA/MAC 13")</td>			(WXGA+); 1400 x 1050 (SXGA+); 1366 x 768 (WXGA); 1360 x 768 (WXGA); 1280 x 1024 (Maximum resolution of digital input); 1280 x 1024 (SXGA); 1280 x 1024 (MAC 23"); 1280 x 960 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 1152 x 870 (MAC 21"); 1152 x 864 (XGA); 1024 x 768 (XGA); 832 x 624 (MAC 16"); 800 x 600 (SVGA); 720 x 576 SDTV 480p/480i; 720 x 576 (DVD progressive); 720 x 480 SDTV 576p/576i; 720 x 480 (SDTV 480p); 640 x 480 (VGA/MAC 13")
ENDIRING Output 1 xMm 0 ab 15 pin FDM ippl 2 xMm 0 ab 25 pin FDM ippl 2 xMm 0 ab 25 pin Video ippl 1 x BCA Audio ippl 1 x BCA Madeo ippl 1 x MO ab 3pin (PS 322) (mole) LAN 1 x MAR 0. Bid Pin (PS 322) (mole) Madeo Control Madeo Madoo Madoo Madeo Control Am 0 Magin Madeo Control Madeo Madoo Madoo Madeo Control Madeo Madoo Madoo Madeo Control Madeo Control Auto Madoo Madoo Madoo Control Auto Madoo Contr			
Vide Impail 1x RCA Audio Impail 1x RCA Audio Impail 1x RCA Audio Impail 1x SD mm Steeke Mini Jack (1x RCA Steeke Output 1x 35 mm Steeke Mini Jack (Vynamie mer / Condenser mis) Control Impail 1x 35 mm Steeke Mini Jack (Vynamie mer / Condenser mis) Control Impail 1x 35 mm Steeke Mini Jack (Vynamie mer / Condenser mis) Control Impail 1x 35 mm Steeke Mini Jack (Vynamie mer / Condenser mis) Control Impail 1x AR48, Optional WLAN USB 1x Type A COSE 20 (mis) ADD Sync Output 1x Min ON Sync Object Output 1x Min ON Sync Video Signals NISC: NTSO 4.42, PM, PMA.46, SEEDM REFORE CONTROL Benetic Control Appet 1x Min ON Sync Option 1x Min ON Sync Top 240 VA, SS 6 0 filz Penetic Control REFORE CONTROL Mont Sync Top 240 VA, SS 6 0 filz Penetic Control Auto Appet Prevention and Mink and Control Auto Appet Prevention and Appet Prevention Appet Prevention Appet	CONNECTIVITY		Output: 1 x Mini D-sub 15 pin
Adia Instit 1 x 3 mm Sizero Min Jack (1 x RDA Sizero Ougot 1 x 3 mm Sizero Min Jack (1 x RDA Sizero Ougot 1 x 3 mm Sizero Min Jack (1 x RDA Sizero Outor 1 x 3 mm Sizero Min Jack (1 x RDA Sizero Min Jack (1			
Image in the second s		Video	Input: 1 x RCA
Exted Input: 1 x D Sub 9 pin (RS 232) (male) LN 1 x R45; Optional WLAN LAN 1 x R45; Optional WLAN B30 spine Optional WLAN Constraint Spine Vieleo Signals NTSC: NTSC 44.8 PAL; PALA PLAGE, SECMA REMOTE CONTROL Remote Control Adject Extraint More Stapping Power Stapping 100 240 VA; Coi - 60 itz Power Stapping 100 240 VA; Coi - 60 itz Power Stapping 100 240 VA; Coi - 60 itz Power Stapping 100 240 VA; Coi - 60 itz Power Stapping 100 240 VA; Coi - 60 itz Power Stapping 100 240 VA; Coi - 60 itz Power Stapping 20 formani/ 24 (Ficia): 20 (Mewark Stand by) / 04 (Stand-by); 335 (Fidipi Bright) MERATINEL Starge Temperature (Ci 30 itag Starge Temperature (Ci 10 to 50 10 to 50 Starge Temperature (Ci 10 to 50 10 to 50 Starge Temperature (Ci 10 to 50 10 to 50 Starge Temperature (Ci 10 to 50 10 to 50 Starge Temperature (Ci 10 to 50 10 to 50		Audio	Output: 1 x 3.5 mm Stereo Mini Jack (variable)
IAN 1x 8/48, Optional WLAN USB 1x Type A (USB 2.0 high speed) 1x Type B 30 Synce Output 1 x Min IDN Spin Web Go Signals NTS: NTS 4.48, PLP. MA MEL60, SECAM REMOTE CONTROL Remote Control Aspect Facio, Audio Control, Auto Adjust, Automatic Picture Adjustment, AV Mute; Digital Zoom; Freeze, Help Eco Mode; D set, Meystone Concerton: Lany Mode Control, Mogrity Function, Optional Presentation and Mouse Control, Picture Adjust, Source Select ELECTRICAL Power Supply 0.040 VA (2: 6) of 0.12 Method Signals S7.9 x 97.5 x 28.5 (without lens and feet) Weight (kg) 3.6 Fan Noise (BB (A)] 30 / 30 / 36 (ECO / Normal / High Bright) Berostonic (W xH x2) (mm) 36.7 9 x 97.5 x 28.5 (without lens and feet) Weight (kg) 3.6 Fan Noise (BB (A)] 30 / 30 / 36 (ECO / Normal / High Bright) Bronze (BB (A)] 30 / 30 / 36 (ECO / Normal / High Bright) Bronze (BB (A)] 30 / 30 / 36 (ECO / Normal / High Bright) Bronze (BB (A)] 30 / 30 / 36 (ECO / Normal / High Bright) Bronze (BB (A)] 30 / 30 / 36 (ECO / Normal / High Bright) Bronze (BB (A)] 30 / 30 / 36 (ECO / Normal / High Bright) Bronze (BB (A)]		Microphone	Input: 1 x 3.5 mm Monaural Mini Jack (Dynamic mic / Condenser mic)
Ising Ising Pa (USB 2.0 high speed): I x Type B 30 Sync Output: 1 X Min DIN 3pin Video Signals NTSC, NTSC ALS, PAL: PAL-M, PAL60; SECMA ERFORCE CONTROL Power Suppi Output: 1 X Min DIN 3pin ELECTRICAL Power Suppi 00-204 VA 42; 96-10 Control, Auto Adjust, Automatic Picture Adjustment, AV Multe; Digital Zoom, Freeze, Help Eco Mode, DI set Reyctore Contrection; Lamp Mode Control, Magnify/function; Optional Presentation and Mouse Control, Picture Adjust: Source Select ELECTRICAL Power Suppi 00-204 VA 42; 96-10-10 MERCHANICAL Power Suppi 00-204 VA 42; 96-10-10 Memosions (W X H x D) (mm) Si7.9 x 97.5 x 285.9 (without lens and feet) Memosions (W X H x D) (mm) Si7.9 x 97.5 x 285.9 (without lens and feet) Memosions (W K H x D) (mm) Si7.9 x 97.5 x 285.9 (without lens and feet) Memosions (W K H x D) (mm) Si7.9 x 97.5 x 285.9 (without lens and feet) Memosions (W K H x D) (mm) Si7.9 x 97.5 x 285.9 (without lens and feet) Memosions (W K H x D) (mm) Si7.9 x 97.5 x 285.9 (without lens and feet) Memosions (W K H x D) (mm) Si7.9 x 97.5 x 285.9 (without lens and feet) Memosions (W K H x D) (mm) Si7.9 x 97.5 x 285.9 (without lens and feet) Memosions (W K H x D) (Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
Bit Sync Output 1 x Mini DIN 3g in Video Signals NTSC. V132 V.43. PAL, PALM, PALM, PALKOS SECAM REMOTE CONTROL Remote Control Aspect Ratio, Audio Control, Audo Adjust: Automatic Picture Adjustment, AV Mate, Digital Zoom; Freeze, Help Eco Mode; Di Sec ELECTRICAL Power Supply 100-240 V.A; 50 - 60 Hz Meechanical Power Supply 100-240 V.A; 50 - 60 Hz Meechanical Power Supply 100-240 V.A; 50 - 60 Hz Meechanical Power Supply 100-240 V.A; 50 - 60 Hz Meechanical Power Supply 100-240 V.A; 50 - 60 Hz Meechanical Power Supply 100-240 V.A; 50 - 60 Hz Meechanical Power Supply 36 F3 9.47 52 x 285 (without lens and feet) Weight [kg] 3.6 Fan Noise [kB (M) 30 / 30 7 80 56 ECO / Normal / High Bright) ENVIRONMENTAL CONDITIONS Operating Humidity [%] 20 to 80 Storage Temperature [*C] -10 to 50 Storage Temperature [*C] -10 to 50 Storage Temperature [*C] -10 to 50 Storage Temperature [*C] -10 to 50 Storage Temperature [*C] -10 to 50 Storage Temperature [*C] -10 to 50		LAN	1 x RJ45; Optional WLAN
Video Signals NTSC, NTSC 4.43, PAL, PAL, AP, PAL, 60, SECAM REMOTE CONTROL Benole Control Appet Falsio, Audio Control, Auto Adjust, Automatic Pature Adjustment, AV Mute: Digital Zonne, Freeze: Help Eno Mode; ID est Keystone Correction; Lamp Mode Control, Magnify-function, Optional Presentation and Mouse Control, Picture Adjust, Source Select (Power Consumption [W] ELECTRICAL Power Supply Dio 240 V AS; 50 - 60 Hz Mechanica Dimensions (W At XD) [mm] 367 9 x 75 x 258 (without lens and feet) Mechanica Dimensions (W At XD) [mm] 367 9 x 75 x 258 (without lens and feet) Mechanica Dimensions (W At XD) [mm] 367 9 x 75 x 258 (without lens and feet) Meight [kg] 3.6 367 Operating Temperature [°C] 6 to 40 36 Operating Humidity [%] 20 to 80 36 Strage Temperature [°C] 36 to 40 36 36 Operating Humidity		USB	1 x Type A (USB 2.0 high speed); 1 x Type B
REMOTE CONTROL Renote Control Aspect Ratio, Audio Control, Auto Adjust, Automatic Picture Adjustment, AV Mute, Digital Zoom, Freeze, Help Eco Mode, ID set, Keystone Corrector, Lamp Mude Control, Magnif-Junction, Optional Presentation and Mouse Control. Picture Adjust, Source Select 100 240 V A/S, 06 - 06 J2 ELECTRICAL Power Supply 100 240 V A/S, 06 - 06 J2 Power Consumption [M] 278 (Normal) / 246 (Eco) / 2 9 (Network Stand-by) / 0.4 (Stand-by). 335 (High Bright) MECHANICAL Dimensions (W x H x D) [mm] 36 7 3 x 97 5 x 285.9 (without lens and feet) Weight [kg] 36 Fan Noise [d6 (A)] 30 / 30 / 36 (ECO / Normal / High Bright) ENVIRONMENTAL CONDITIONS Operating Temperature [°C] 5 to 40 Querating Temperature [°C] 20 to 80 Storage Temperature [°C] 20 to 80 Storage Temperature [°C] 10 to 50 Storage Ad Eignonnics CE EAC, Gost-R: RoHS; TUV GS Specker [M] 1 x 20 (mono) ADDITIONAL FEATURES Specker [M] 1 x 20 (mono) Specker [M] 1 x 20 (mono)		3D Sync	Output: 1 x Mini DIN 3pin
Registione Correction; Lang Mode Control, Magnify-function; Optional Presentation and Mouse Control, Picture Adjust; Source Select ELECTRICA. Power Consumption IVI 278 (Normal/ 226 (Eco:) 7.2 (Network Stand-by) / 0.4 (Stand-by); 335 (High Bright) MEGHANICAL Dimensions (W xH xD) (mm) 36.7 9 x 97.5 x 265.9 (Without lies and feet) Micro Picture Consumption IVI 30.7 30 / 36 (ECO / Normal / High Bright) ENVIRONMENTAL CONDITIONS Operating Temperature (°C) 5 to 4 Orage Funding Vision Vision 20 to 80 ERVIRONMENTAL CONDITIONS Operating Funding Vision 20 to 80 ERVIRONMENTAL CONDITIONS Seles (Bif vi and Ergonomics CE, EAC; Cost-R: Rol-S; TU/ GS ERVIRONMENTAL CONDITIONS Seles (Bif vi and Ergonomics CE, EAC; Cost-R: Rol-S; TU/ GS ERVIRONMENTAL FEATURES Seles (Bif vi and Ergonomics CE, EAC; Cost-R: Rol-S; TU/ GS Sint Pintus Conter Contrating Vision Seles (Visi		Video Signals	NTSC; NTSC 4.43; PAL; PAL-M; PAL60; SECAM
Number of the second	REMOTE CONTROL	Remote Control	Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; AV Mute; Digital Zoom; Freeze; Help Eco Mode; ID set; Keystone Correction; Lamp Mode Control; Magnify-function; Optional Presentation and Mouse Control; Picture Adjust; Source Select
MECHANICAL Dimensions (W x H x D) [mm] 3679 x 97.5 x 285 9 (without lens and feet) Weight [kg] 3.6 Fan Noise [dB (A)] 30/30/36 (ECO / Normal / High Bright) ENVIRONMENTAL CONDITIONS Operating Temperature [°C] 5 to 40 Operating Temperature [°C] -10 to 50 Storage Temperature [°C] -10 to 50 Storage Temperature [°C] -10 to 50 Storage Humidity [%] 20 to 80 EREGONOMICS Safety and Ergonomics CE EAC, Gost PR, RoHS, TÜV GS Speakers [W] 1 x 20 (mono) Ambient Light Senor, Auto Eoo Mode, Auto Power-ON Function, Carbon Savings Meter, Colour Management, Constant Brightness ADDITIONAL FEATURES Special Characteristics Ambient Light Senor, Auto Eoo Mode, Auto Power-ON Function, Carbon Savings Meter, Colour Management, Constant Brightness GREEN FEATURES Energy Efficiency 75 % AV mute function, Auto Eco Mode, Kensington security slot, Kengael Lock, Magnify, NaViSet Administrator 2, Off-Timer, Optional USA to QU South 29 Janguages, Password Security System, Quick Start, Rentot Control and administration via LAN and Brozer South USA South 29 Janguages, Password Security System, Quick Start, Rentot Control and Administration via LAN and Brozer South USA South 29 Janguages, Password Security System, Quick Start, Benote Control and Administration via LAN and Security System Administrator 2, Off-Timer, Optional USA Logg GREEN F	ELECTRICAL	Power Supply	100-240 V AC; 50 - 60 Hz
Weight [kg] 3.6 Fan Noise [dB (A)] 30 / 30 / 36 (ECO / Normal / High Bright) ENVIRONMENTAL CONDITIONS Operating Temperature [°C] 5 to 40 Operating Humidity [%] 20 to 80 ERGONOMICS Safety and Ergonomics CE, EAC, Gost R, RoHS, TÜV GS Storage Humidity [%] 20 to 80 ERGONOMICS Safety and Ergonomics CE, EAC, Gost R, RoHS, TÜV GS Speakers [W] 1 x 20 (mono) ADDITIONAL FEATURES Speakers [W] 1 x 20 (mono) ADDITIONAL FEATURES Special Characteristics Ambient Light Accesson via Network, Creation Rowings Meter, Colour Management, Constant Brightness Mode; Content Transmission via Network, Creation Rowings Meter, Colour Management, Constant Brightness Mode; Content Transmission via Network, Creation Rowings Meter, Colour Management, Constant Brightness Mode; Content Transmission via Network, Creation Rowings Meter, Colour Management, Constant Brightness Mode; Content Transmission via Network, Creation Rowing, NeuViSet Administrator 2, Uf Timer, Optional Use Lioog, Optional WLAN, SDD with 29 languages; Password Security System; Quick Start, Remote control and administration via LAN and RSS2; Security Bar, Simple Access Point USB Vewer for JPEG; Virtual Remote Contol and Administration via LAN and RSS2; Security Bar, Simple Access Point USB Vewer for JPEG; Virtual Remote Contol and Administration via LAN and RSS2; Security Bar, Simple Access Point USB Vewer for JPEG; Virtual Remote Contol and Administration via LAN and RSS2; Security Bar		Power Consumption [W]	278 (Normal) / 246 (Eco) / 2.9 (Network Stand-by) / 0.4 (Stand-by); 335 (High Bright)
Fan Noise (B8 (A)] 30 / 30 / 36 (ECO / Normal / High Bright) ENVIRONMENTAL CONDITIONS Operating Temperature (°C) 5 to 40 Operating Humidity [%] 20 to 80 Storage Temperature (°C) 10 to 50 Storage Temperature (°C) 20 to 80 REGONOMICS Safety and Ergonomics CE, EAC, Gost PR, RoHS, TÜV GS ADDITIONAL FEATURES Safety and Ergonomics CE, EAC, Gost PR, RoHS, TÜV GS ADDITIONAL FEATURES Speakers (W) 1 x 20 (mono) ADDITIONAL FEATURES Speaker S(W) Noisen Light Sensor, Auto Eco Mode; Auto Power-ON Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Content Transmission via Network; Crestron RoomView; DICOM Simulation; Direct Power-Off Function; Full 3D DLP ^a LINK support: High Altitude Mode; Kensington security slot; Keypad Lock Magnify; NaVGset Administratori via LAN and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for d	MECHANICAL	Dimensions (W x H x D) [mm]	367.9 x 97.5 x 285.9 (without lens and feet)
ENVIRONMENTAL CONDITIONS Operating Temperature [*C] 5 to 40 Operating Humidity [%] 20 to 80 Storage Temperature [*C] -10 to 50 Storage Temperature [*C] 20 to 80 ERGONOMICS Safety and Ergonomics CE; EAC; Gost-R; RoHS; TÜV GS Speakers [W] 1 x 20 (mono) ADDITIONAL FEATURES Speakers [W] 1 x 20 (mono) ADDITIONAL FEATURES Special Characteristics Ambient Light Sensor; Auto Eco Mode; Auto Power-ON Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Content Transmission via Network; Crestorn Room/iew; DICOM Simulation, Direct Power-OI Function; Puttorian Juert Opy Puttorian WLAN; OSD with 29 languages; Password Security System; Quick Start; Remote control and administration via LAN and RS223 Security Bar; Simple Access Poin; USB Viewer for JPEG; Virtual Remote Ford ierct PC control, Wall Colour Correction Power Management; Longer Iamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Ecological Materials 100% recyclable packaging; Downloadable manuals; ECO packaging Ecological Standards EPP compliant; RoHs compliant; WEEE WARRANTY Projectors 3 years pan-European service Light Source 6 months, max 1000 hrs IR Remote Control (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users Manual on CD-ROM SplipPING CONTENT		Weight [kg]	3.6
Appending Humidity [%] 20 to 80 Storage Temperature [*C] -10 to 50 Storage Humidity [%] 20 to 80 ERGONOMICS Safety and Ergonomics CE; EAC; Gost-R; RoHS; TÜV GS Speakers [W] 1 x 20 (mono) ADDITIONAL FEATURES Special Characteristics Ambient Light Sensor, Auto Eoo Mode; Auto Power-ON Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Cocentm Transmission via Network; Crestron Room/iew; DICOM Simulation, Direct Power-Off Function; Full 3D DLP ^b LINK support; High Altitude Mode; Kensor, Auto Eoo Mode; Auto Power on Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Cocentm Transmission via Network; Crestron Room/iew; DICOM Simulation, Direct Power-Off Function; Full 3D DLP ^b LINK support; High Altitude Mode; Kensor, Auto Eoo Mode; EOO scheduler; Green one touch ECO and Administrator 2; Off-Timer; Optional User Logo; Optional User Logo; Optional WLAN; OSD with 29 languages; Password Security System; Quick Start; Remote control and administration via LAN and RS222. Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote control and administration via LAN and RS222. Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote control, Wall Colour Correction RS222. Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote control, Wall Colour Correction RS222. Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote control, Wall Colour Correction RS222. Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote control, Wall Colour Correction RS222. Security Bar; Simple Acceess Point; USB Viewer for JPEG; Virtual Remote con		Fan Noise [dB (A)]	30 / 30 / 36 (ECO / Normal / High Bright)
Storage Temperature [°C] -10 to 50 Storage Humidity [%] 20 to 80 ERGONOMICS Safety and Ergonomics CE; EAC; Gost R; RoHS; TÜV GS Speakers [W] 1 x 20 (mono) ADDITIONAL FEATURES Special Characteristics Ambient Light Sensor, Auto Eco Mode; Auto Power-ON Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Content Transmission via Network; Crestron RoomView; DICOM Simulation; Direct Power-Off Function; Full 3D DLP® LINK soupport; High Altitude Mode; Kensington security slot; Keypad Lock, Magnify; NaViSet Administrator 2; Off Timer; Optional User Logo; Optional WLAN; OSD with 29 Janguages; Password Security System, Quick Start, Remote control and administration via LAN and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote For direct PC control; Wall Colour Correction and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote For direct PC control; Wall Colour Correction and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction and	ENVIRONMENTAL CONDITIONS	Operating Temperature [°C]	5 to 40
Storage Humidity [%] 20 to 80 ERGONOMICS Safety and Ergonomics CE; EAC; Gost-R; RoHS; TÜV GS ADDITIONAL FEATURES Special Characteristics Ambient Light Sensor, Auto Eco Mode; Auto Power-ON Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Content Transmission via Network; Crestron RoomView; DICOM Simulation, Direct Power-Off Function; Full 3D DLP [®] LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify, NaVSet Administrator 2, Off-Timer, Stul 3D DLP [®] LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify, NaVSet Administrator 2, Off-Timer, Stul 3D DLP [®] LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify, NaVSet Administrator 2, Off-Timer, Stul 3D OLP [®] LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify, NaVSet Administrator 2, Off-Timer, Stul 3D OLP [®] LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify, NaVSet Administrator 2, Off-Timer, Stul 3D OLP [®] LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify, NaVSet Administrator 2, Off-Timer, Stul 3D OLP [®] LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify, NaVSet Administrator 2, Off-Timer, Stul 3D OLP [®] LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify, NaVSet Administrator 2, Off-Timer, Stul 3D OLP [®] LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify, NaVSet Administrator 2, Off-Timer, Stul 3D Stul 2D Content To Stul Adverses Rearry Efficiency Fife-compliant; Rel-KecsoPrine; Natore Construction; Only 0.4W stand-by; Software scheduling Power Management; Longer lank; ECO packaging Management;		Operating Humidity [%]	20 to 80
ERGONOMICS Safety and Ergonomics CE; EAC; Gost-R; RoHS; TÜV GS ADDITIONAL FEATURES Speakers [W] 1 x 20 (mono) ADDITIONAL FEATURES Special Characteristics Ambient Light Sensor; Auto Eco Mode; Auto Power-ON Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Content Transmission via Network; Crestron RoomView; DICOM Simulation; Direct Power-Off Function; Full 3D DLP® LINK support; High Altitude Mode; Kensington security Slot; Keypad Lock; Magnify; NaViSet Administrator 2; Off-Timer; Optional USEr Logo; Optional WLAN; OSD with 29 languages; Password Security System; Quick Start; Remote control and administration via LAN and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction SPEAM The Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Ecological Standards WARRANTY Projectors 3 years pan-European service SHPPING CONTENT Shipping Contents R Remote Control (RD-469E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users Manual on CD-ROM OPTIONAL ACCESSORIES Optional Accessories 3D Starter Kit (PJ02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Lamp (NP30LP); Universal		Storage Temperature [°C]	-10 to 50
Speakers [W] 1 x 20 (mono) ADDITIONAL FEATURES Speakers [W] Ambient Light Sensor; Auto Eco Mode; Auto Power-ON Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Content Transmission via Network; Crestron RoomView; DICOM Simulation; Direct Power-Off Function; Full 3D DLP® LINK support; High Altitude Mode; Kensington security slot; Keypad Lock, Magnify; NaViSet Administrator 2; Off-Timer; Optional User Logo; Optional WLAN; OSD with 29 language; Password Security System; Quick Start; Remote control and administration via LAN and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Foorgical Standards For Congliant; Not Security Sticker; Soft Case; User Light Source Sipping C		Storage Humidity [%]	20 to 80
Speakers [W] 1 x 20 (mono) ADDITIONAL FEATURES Special Characteristics Ambient Light Sensor; Auto Eco Mode; Auto Power-ON Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Content Transmission via Network; Crestron RoomView; DICOM Simulation; Direct Power-Off Function; Full 3D DLP® LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify; NaViSet Administrator 2; Off-Timer; Optional User Logo; Optional WLAN; OSD with 29 languages; Password Security System; Quick Start; Remote control and administration via LAN and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Power Management; Longer lamp life; Reduced po	ERGONOMICS	Safety and Ergonomics	CE; EAC; Gost-R; RoHS; TÜV GS
Mode; Content Transmission via Network; Crestron RoomView; DICOM Simulation; Direct Power-Off Function; Full 3D DLP® LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify; NaViSet Administrator 2; Off-Timer; Optional User Logo; Optional WLAN; OSD with 29 languages; Password Security System; Quick Start; Remote control and administration via LAN and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction GREEN FEATURES Energy Efficiency 75 % AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button; ImageCare® Technology; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Ecological Materials 100% recyclable packaging; Downloadable manuals; ECO packaging WARRANTY Projectors 3 years pan-European service SHIPPING CONTENT Shipping Contents II R Remote Control (RD-469E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users Manual on CD-ROM Optional Accessories Optional Accessories 3D Starter Kit (PJ02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Lamp (NP30LP); Universal		Speakers [W]	1 x 20 (mono)
Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling Ecological Materials 100% recyclable packaging; Downloadable manuals; ECO packaging Ecological Standards ErP compliant; RoHs compliant; WEEE WARRANTY Projectors 3 years pan-European service Light Source 6 months, max. 1000 hrs SHIPPING CONTENT Shipping Contents IR Remote Control (RD-469E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users OPTIONAL ACCESSORIES Optional Accessories 3D Starter Kit (PJ02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Lamp (NP30LP); Universal	ADDITIONAL FEATURES	Special Characteristics	Ambient Light Sensor; Auto Eco Mode; Auto Power-ON Function; Carbon Savings Meter; Colour Management; Constant Brightness Mode; Content Transmission via Network; Crestron RoomView; DICOM Simulation; Direct Power-Off Function; Full 3D DLP® LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify; NaViSet Administrator 2; Off-Timer; Optional User Logo; Optional WLAN; OSD with 29 languages; Password Security System; Quick Start; Remote control and administration via LAN and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction
Ecological Standards ErP compliant; RoHs compliant; WEEE WARRANTY Projectors 3 years pan-European service Light Source 6 months, max. 1000 hrs SHIPPING CONTENT Shipping Contents IR Remote Control (RD-469E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users Manual on CD-ROM OPTIONAL ACCESSORIES Optional Accessories 3D Starter Kit (PJ02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Lamp (NP30LP); Universal	GREEN FEATURES	Energy Efficiency	
WARRANTY Projectors 3 years pan-European service Light Source 6 months, max. 1000 hrs SHIPPING CONTENT Shipping Contents IR Remote Control (RD-469E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users Manual on CD-ROM OPTIONAL ACCESSORIES Optional Accessories 3D Starter Kit (PJ02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Lamp (NP30LP); Universal			
Image: content of the source 6 months, max. 1000 hrs SHIPPING CONTENT Shipping Contents IR Remote Control (RD-469E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users Manual on CD-ROM OPTIONAL ACCESSORIES Optional Accessories 3D Starter Kit (PJ02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Lamp (NP30LP); Universal		Ecological Standards	ErP compliant; RoHs compliant; WEEE
SHIPPING CONTENT Shipping Contents IR Remote Control (RD-469E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users Manual on CD-ROM OPTIONAL ACCESSORIES Optional Accessories 3D Starter Kit (PJ02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Lamp (NP30LP); Universal	WARRANTY	Projectors	3 years pan-European service
Manual on CD-R0M OPTIONAL ACCESSORIES Optional Accessories 3D Starter Kit (PJ02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Lamp (NP30LP); Universal		Light Source	6 months, max. 1000 hrs
	SHIPPING CONTENT	Shipping Contents	IR Remote Control (RD-469E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Soft Case; Users Manual on CD-ROM
	OPTIONAL ACCESSORIES	Optional Accessories	3D Starter Kit (PJ02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Lamp (NP30LP); Universal Ceiling Mounts (PJ01UCM); Wireless LAN module (NP05LM)

¹ Compliance with ISO21118-2005

