

# NEC V311W

Order Code: 60003636

# **NEC V311W Value Projector**

Get the Ultimate 3D Experience with the V311W DLP®Projector. The compact size in combination with light weight makes it easy to place it wherever you need it. With 3100 ANSI lumens brightness and higher contrast this compact projector is recommended for screen sizes of up to 110" diagonal. V311W is Nvidia certified to ensure plug and play operation especially for 3D gaming and 3D photography.

The V311W is the perfect solution for small meeting rooms as well as classrooms.



## **DELIVERING GENUINE BENEFITS**

Control and Monitoring - via RS-232.

Green EcoMode Button - on remote.

**Higher Efficiency, Lower Power Consumption** - full ErP compliance.

Long Lamp Life - up to 5000 hrs.

Virtual Remote - for direct PC control.

**3D ready -** future-proof DLP®-Link<sup>™</sup> technology with 120Hz and Top/Bottom, 60Hz.

**Free Download of Multi-Display Management Software** - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



### **OUTSTANDING PERFORMANCE**

- Excellent and Brilliant Colours due to VIDI technology
- . Contrast 3000:1
- . High Brightness 3100 ANSI lumens
- . Quick Start Direct Power Off
- . 7W Speaker
- Carbon Meter indicating the reduced amount of CO<sup>2</sup> emissions by the use of ECO mode



#### **SPECIAL CHARACTERISTICS**

3D ready DLP®-Link<sup>™</sup>, 120Hz and Top/Bottom, 60Hz, 6-segment Colour Wheel, Auto Power Start, BrilliantColor<sup>™</sup> and VIDI technology, Carbon Savings Meter, Crestron RoomView, Intelligent Power Management, Long Life Lamp, Manual vertical Keystone Correction (V= ±40°), NaViSet Administrator 2, Plug & Play, Quick-Start-/Direct-Power-Off Function, Virtual Remote for direct PC control, 100% recyclable packaging, Downloadable manuals, RoHs compliant, ErP compliant, WEEE

Energy Efficiency	Intelligent Power Management
Ecological Materials	100% recyclable packaging; Downloadable manuals
Ecological Standards	RoHs compliant; ErP compliant; WEEE

#### **Technical Specification NEC V311W** IMAGE Projection Technology 1 x 1.65 cm (0.65") 2x LVDS DMD Chip Native Resolution 1280 x 800 (WXGA) 3000.1 Contrast Ratio 1 3100 ANSI Lumen Brightness 1 Lamp 225 W AC Lamp Life [hrs] 3000 (5000 Eco Mode) Projection Factor 1.55 - 1.7 : 1 Projection Distance [m] 1 - 11 Screen Size (diagonal) [cm] / [inch] Minimum: 76; Maximum: 762 Zoom Manual Focus Adjustment Manual Supported Resolutions Up to 1920x1080 Horizontal: 15-100 kHz (RGB: 24 kHz- 100 kHz); Vertical: 50 - 120 Hz Frequency CONNECTIVITY RGB (analog) Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin HDMI™ Input: 1 x HDMI<sup>™</sup> (Deep Color, Lip sync) Video Input: 1 x RCA S-Video Input: 1 x Mini DIN 4-pin Audio Input: 2 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo for Video and S-Video Output: 1 x 3.5 mm Stereo Mini Jack Control Input: 1 x D-Sub 9 pin (RS-232) (male) ΙΔΝ 1 x R I45 Video Signals PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M REMOTE CONTROL Remote Control Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; Freezefunction; Help-function; ID set; Keystone Correction; Lamp Mode Control; Magnify-function; Picture Adjust; Picture Mode; Picture Mute; Source Select ELECTRICAL Power Supply 100-240 V AC: 50 - 60 Hz Power Consumption [W] 268 max.; 210 Eco Mode; 0.5 Power Savings Mode MECHANICAL Dimensions (W x H x D) [mm] 310 x 95 x 247 (without lens and feet) Weight [kg] 2.5 Fan Noise [dB (A)] 33 / 37 (Eco / Normal) ERGONOMICS Safety and Ergonomics CE; ErP; TÜV GS; RoHS Speakers [W] 1 x 7 (mono) WARRANTY Projectors 3 years pan-European service Lamn 6 months, max, 1000 hrs SHIPPING CONTENT Shipping Contents User Manual on CD-ROM (Russian Manual in Hardcopy); Projector; IR Remote Control (RD-448E); Mini D-SUB Signal Cable (1.8 m); Power Cord; Quick Setup Guide; Lens Cap OPTIONAL ACCESSORIES Optional Accessories 3D Starter Kit (NP01SK3D); DLP-Link 3D Glasses (NP01GL/NP02GL); Lamp (NP18LP); Mouse Receiver (NP01MR); Universal Ceiling Mounts (NP01/02/03/04/05UCM)

<sup>1</sup> Compliance with ISO21118-2005

