

Empowered by Innovation



Professional Installation Projectors

PH Series

NP-PH1201QL



Powerful installation projectors equipped to take on the most demanding integration projects

Video & Graphics Processing

- Up to 60fps 4096 x 2160 pixels sequential input via single cable (Display Port 1.2)
- Dual Pipe input capability (2 x Display Port 1.2)
- 3D Capable
- Scaling of HDMI formats to fill the 4k display
- HDMI for Side by Side, Frame Packing & Top Bottom Formats
- Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources (example 144Hz display)
- Two sources in parallel for Left and Right Eyes

Image Blanking

- Linear black "curtains" adjustable for all four edges

Color adjustments

- Up to 12 bits per color processing (depending on source and input type)
- Degamma table maps 12 bit input to 16 bit palette (R, G & B) for display
- Individual R, G & B gain and bias controls

3D Functionality

- Full 4k 3D display capability
- Dual Pipe: Left and Right channels input separately to projector in parallel, then interleaved for sequential display
- Synchronization of active glasses
- Adjustable Dark Time and Sync Offset for optimization of ghosting and smooth grayscale for switching switching glasses and polarizers
- HDMI input signals will be scaled to the DMD resolution.

Edge blending

- High bit-depth blending up to 20% of the image width on all four sides of the DMD (approximately 800 pixels overlap per edge)
- Black level adjustment of the blended area to create different overlap areas
- Correction for non-active pixels at the edge of the display



Projector Control

- Keypad with LCD panel
- Network control via RJ45 and protocol
- Group Controller Application

NP-PH1201QL



UNIQUE FEATURES

WARRANTY

Registered owners receive a 3-year parts and labor warranty including the first year of InstaCare. The laser module is covered for 1 year. InstaCare provides the original owner one year of either limited 3 business day repair/return or next business day exchange.

IN THE BOX

User's manual on CD-ROM, Important Info, lens adapter for NC lens, lens gear cover, Security Key for cabinet, Warranty Sheet

ORDERING MODEL NUMBERS

NP-PH1201QL

Specifications for NP-PH1201QL

<p>OPTICAL</p> <p>Display Technology Light Output (lumens)</p> <p>Resolution Native Maximum Contrast Ratio (up to)</p> <p>Laser Life (up to) Screen Size (diagonal) Throw Ratio L2K-10F1 NC-50LS12Z NC-50LS14Z NC-50LS16Z NC-50LS18Z NC-50LS21Z L2K-43ZM1 L2K-55ZM1</p> <p>Projection Distance Projection Angle Lens* Zoom Zoom Ratio</p> <p>Focus F-number, f-number L2K-10F1 NC-50LS12Z NC-50LS14Z NC-50LS16Z NC-50LS18Z NC-50LS21Z L2K-43ZM1 L2K-55ZM1</p> <p>Shift</p>	<p>1.38" DMD</p> <p>12,000 normal / Eco = variable</p> <p>DC4K 4096x2160 QXGA 4096x2160 2000:1 with auto iris</p> <p>20,000 hours 80 to 500 in. / 2.03 to 12.7m</p> <p>0.9:1 1.13 - 1.66:1 1.30 - 1.85:1 1.45 - 2.17:1 1.63 - 2.71:1 1.95 - 3.26:1 3.70 - 5.30:1 4.80 - 7.40:1</p> <p>Variable Variable</p> <p>Powered w/Lens Memory Lens Dependent</p> <p>Powered w/Lens Memory</p> <p>TBD TBD 40.6 - 57.8mm 45.2 - 64.04mm 50.9 - 85.2mm 60.8 - 102.3mm TBD TBD</p> <p>Powered +0.5/-0 vertical, +0.06/-0.08 horizontal</p>
<p>SIGNAL COMPATIBILITY/CONNECTIVITY</p> <p>Scan Rate Horizontal Vertical</p> <p>Supported Video Standards SD/HD Video Signal Compatibility PC Signal Compatibility DisplayPort / HDMI</p> <p>Macintosh Compatibility Input/Output Terminals RGB1 (digital) RGB2 (digital) RGB3 (digital) RGB4 (digital) External Control Sync Compatibility</p>	<p>15 - 108 kHz 48 - 120 Hz</p> <p>NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM 1080p, 1080i, 720p, 576p, 576i, 480p, 480i</p> <p>4096 x 2160p @ 60 / 59.94 / 50 / 30 / 25 / 24 / 23.98 Hz 3840 x 2160p @ 60 / 59.94 / 50 / 30 / 25 / 24 / 23.98 Hz 2048 x 1080p and 1920 x 1080 @ 60 / 59.94 / 50 / 30 / 25 / 24 / 23.98 Hz 2048 x 1080p and 1920 x 1080 @ 60 / 59.94 / 50 / 30 / 25 / 24 / 23.98 Hz 1920 x 1080i 60 Hz</p> <p>Yes</p> <p>HDMI w/HDCP HDMI w/HDCP DisplayPort w/HDCP DisplayPort w/ HDCP RS-232, Wired Remote, USB (Service Port0) Separate Sync / Composite Sync / Sync on G</p>
<p>ELECTRICAL</p> <p>Power Requirements Input Current Power Consumption (ECO off/ECO Mode/Standby/ Standby-Power Saving)</p>	<p>200 - 240V AC, 50/60Hz 8.2A 1608W</p>
<p>MECHANICAL</p> <p>Optional Lenses Installation Orientation Dimensions (WxDxH) Net Weight Fan Noise Regulations</p>	<p>NC-50LS12Z, NC-50LS14Z, NC-50LS16Z, NC-50LS18Z, NC-50LS21Z, L2K-30ZM</p> <p>Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear 27.5 x 36.8 x 12.7 in. / 700 x 935 x 323 mm 148.9 lbs. / 67.5 kg 48 dB USA: UL 1950 FCC Class B, Canada: CSA950 (C-UL), NOM</p>
<p>ENVIRONMENTAL</p> <p>Operating Temperature Humidity Storage</p>	<p>50° - 95°F / 10° - 35°C 20-80% non-condensing 14° - 122°F / -10° - 50°C</p>
<p>ACCESSORIES</p> <p>L2K-10F1 NC-50LS12Z NC-50LS14Z NC-50LS16Z NC-50LS18Z NC-50LS21Z L2K-43ZM1 L2K-55ZM1 NC-80DS02</p>	<p>0.9:1 fixed lens 1.13 - 1.66 zoom lens 1.30 - 1.85 zoom lens 1.45 - 2.17 zoom lens 1.63 - 2.71 zoom lens 1.95 - 3.89 zoom lens 3.70-5.30 zoom lens 4.80-7.40 zoom lens Quad HSDSI, 2 x DVI (HDCP)</p>

* Lens does not ship with the projector.
Additional accessories are available, including screens, carts, mount accessories and replacement cables. Visit www.necdisplay.com for details.



COMPLIES WITH 21 CFR 1040.10 RAYONNEMENT LASER NE PAS FRÉQUER LE FABRICAU DU REGARD LASERSTRALUNG NICHT IN DEN STRAHLE SCHAUEN

CLASS 3R LASER PRODUCT LASERPRODUKT DER KLASSE 3R

WAVE LENGTH: 455-470nm 波長: 455-470nm 波長: 455-470nm

MAX OUTPUT: 330mW 最大出力: 330mW 最大出力: 330mW

REC-EN 60825-1:2007 REC-EN 60825-1:2007 REC-EN 60825-1:2007

LASER APERTURE
避免受到從本窗口射出的激光輻射的照射

ECO Mode is a trademarks of NEC Display Solutions. HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

©2015 NEC Display Solutions of America, Inc. and the NEC logo are registered trademarks of NEC.

Cat.No. 25.NEC.80.GL.UN.189 | Rev. 04.06.2015

NEC Display Solutions

500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE

www.necdisplay.com