

Ultra-High-Brightness 3-Chip DLP™ SOLID SHINE Laser Projectors Excel in 30,000-Im Range



PT-RZ31K Series		
	PT-RZ31K	PT-RS30K
Brightness	31,000 Im (Center), 30,000 Im*	
Resolution	WUXGA	SXGA+
Contrast	20,000:1	

* Measured according to strict international ISO 21118 standards

Original Technology for Elite Performance

- Combines 3-Chip DLP™ with Proprietary SOLID SHINE Laser Technology for Bright and Immersive Picture Quality
- Accurate Rec. 709-compliant Color-space Reproduction
- Dual-Drive Laser Optical Engine Ensures Reliable 24/7 Operation
- Minimal Maintenance Required Under Continuous Operation*1
- Dustproof Design Featuring Hermetically Sealed Laser Modules, Long-life Eco Filter, and Refined Air-intake System
- Efficient Cooling System for Stable Operation in Ambient Temperatures of Up to 45 °C (113 °F)*2

Magnificent Image Quality and Reliable Operation

- 31,000 Im*3 Brightness from an Exceptionally Compact and Lightweight Body
- Real Motion Processor 120 Hz Frame-creation Technology for Smooth Motion Reproduction
- Dynamic Contrast Laser Light-source Modulation Achieves High 20,000:1 Contrast*4
- Detail Clarity Processor 5 Clarifies and Enhances Fine Details with Advanced Processing Algorithm
- System Daylight View 3 Improves Color Perception in Bright Environments and in Mapping Applications
- Quiet Operation with Original Cooling Technology

Versatile System and Installation Flexibility

- Free 360-degree Installation (Vertical and Horizontal)
- Shares Optional Lenses with Panasonic 3-Chip DLP™ Projector Family
- DIGITAL LINK Supports Transmission of Uncompressed Full HD Video and Control Commands Through a Single CAT 5e or Higher STP Cable for Distances of Up to 150 m (492 ft)*5
- Eyebolt Multi-rigging Compatibility
- Multiple Projector Stacking Available without Frame
- Convenient One-Box Design
- Multi-Screen Support System Seamlessly Connects Multiple Screens
- Multi-Unit Brightness and Color Control
- Geometry Manager Pro and Optional Upgrade Kit (ET-UK20 Series)

Specifications (Tentative)

Model	PT-RZ31K	PT-RS30K	
Power supply	AC 200–240 V, 50/60 Hz; AC 100–200 V, 50/60 Hz (brightness is restricted with lower voltage)		
Power consumption	TBD		
DLP™ chip	Panel size	24.4 mm (0.96 inches) diagonal (16:10 aspect ratio)	
	Display method	DLP™ chip × 3, DLP™ projection system	
	Pixels	6,912,000 (1920 × 1200 × 3) pixels	
Refresh rate	120 Hz*1		
Lens	Optional (no lens included with this model)		
Light source	Laser diodes		
Screen size (diagonal)	1.78–25.4 m (70–1,000 in) with 16:10 aspect ratio 1.78–15.24 m (70–600 in) with the ET-D75LE8, 16:10 aspect ratio 3.05–15.24 m (120–600 in) with the ET-D75LE95, 16:10 aspect ratio	1.78–25.4 m (70–1,000 in) with 4:3 aspect ratio 1.78–15.24 m (70–600 in) with the ET-D75LE8, 4:3 aspect ratio 3.05–15.24 m (120–600 in) with the ET-D75LE95, 4:3 aspect ratio	
Brightness	31,000 lm (Center)/30,000 lm ² (High Mode)*3		
Center-to-corner uniformity*2	90 %		
Contrast*2	20,000:1 (Full On/Full Off, Dynamic Contrast Mode: 3)		
Resolution	1920 × 1200 pixels		
Scanning frequency	SD-SDI	SMPTTE ST 259 compliant, [YCbCr 4:2:2 10-bit] 480i, 576i	
	HD-SDI	SMPTTE ST 292 compliant, [YPbPr 4:2:2 10-bit] 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/25p, 1080/24p, 1080/24sF, 1080/30p	
	Dual-link HD-SDI	SMPTTE ST 372 compliant, [RGB 4:4:4 12-bit/10-bit] 1080/60i, 1080/50i, 1080/25p, 1080/24p, 1080/24sF, 1080/30p, 2048 × 1080/24p, 2048 × 1080/25p, 2048 × 1080/30p, 2048 × 1080/30p	
	3G-SDI	SMPTTE ST 424 compliant, [RGB 4:4:4 12-bit/10-bit] 1080/60i, 1080/50i, 1080/25p, 1080/24p, 1080/24sF, 1080/30p, 2048 × 1080/24p, 2048 × 1080/25p, 2048 × 1080/30p, [YPbPr 4:2:2 10-bit] 1080/60p, 1080/50p, 2048 × 1080/48p, 2048 × 1080/50p, 2048 × 1080/60p, 2048 × 1080/50p, 2048 × 1080/30p	
	Dual-link 3G-SDI	SMPTTE ST 425 compliant, [YPbPr 4:4:4 12-bit/10-bit] 1080/60p, 1080/50p, 2048 × 1080/60p, 2048 × 1080/50p, 2048 × 1080/48p, [RGB 4:4:4 12-bit/10-bit] 1080/60p, 1080/50p, 2048 × 1080/60p, 2048 × 1080/50p, 2048 × 1080/48p	
	HDMI/DVI-D/DIGITAL LINK	Compatible with HDCP, 480*4, 576i*4, 480p, 576p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/24p, 1080/24sF, 1080/25p, 1080/30p, 1080/60p, 1080/50p, 640 × 400–WUXGA*5 (1920 × 1200) (compatible with non-interlaced signals only), dot clock: 25–162 MHz	
	RGB	fh: 15–100 kHz, fv: 24–120 Hz, dot clock: 20 MHz–162 MHz	
	YPbPr (YCbCr)	fh: 15.73 kHz, fv: 59.94 Hz [480i (525i)], fh: 15.63 kHz, fv: 50 Hz [576i (625i)], fh: 31.47 kHz, fv: 59.94 Hz [480p (525p)], fh: 31.25 kHz, fv: 50 Hz [576p (625p)], fh: 45.00 kHz, fv: 60 Hz [720 (750)/60p], fh: 37.50 kHz, fv: 50 Hz [720 (750)/50p], fh: 33.75 kHz, fv: 60 Hz [1080 (1125)/60i], fh: 28.13 kHz, fv: 50 Hz [1080 (1125)/50i], fh: 28.13 kHz, fv: 25 Hz [1080 (1125)/25p], fh: 27.00 kHz, fv: 24 Hz [1080 (1125)/24p], fh: 27.00 kHz, fv: 48 Hz [1080 (1125)/24sF], fh: 33.75 kHz, fv: 30 Hz [1080 (1125)/30p], fh: 67.50 kHz, fv: 60 Hz [1080 (1125)/60p], fh: 56.25 kHz, fv: 50 Hz [1080 (1125)/50p]	
	Video/YC	fh: 15.73 kHz, fv: 59.94 Hz (NTSC/NTSC4.43/PAL-M/PAL60), fh: 15.63 kHz, fv: 50 Hz (PAL/PAL-N/SECAM)	
	Optical axis shift*6	Vertical (from center of screen) Horizontal (from center of screen)	±55 % (±44 % with ET-D75LE6, ±68 % – +78 % with ET-D75LE95) (powered) ±20 % (±15 % with ET-D75LE6, ±12 % with ET-D75LE95) (powered) ±50 % (±40 % with ET-D75LE6, +67 % – +71 % with ET-D75LE95) (powered) ±30 % (±20 % with ET-D75LE6, ±8 % with ET-D75LE95) (powered)
Keystone correction range	Vertical: ±40 ° (±22 ° with ET-D75LE50, ±28 ° with ET-D75LE6), Horizontal: ±15 °		
Keystone correction range with optional Upgrade Kit ET-UK20	Vertical: ±45 ° (±40 ° with ET-D75LE10/20, ±22 ° with ET-D75LE50, ±28 ° with ET-D75LE6), Horizontal: ±40 ° (±15 ° with ET-D75LE50/6), Up to a total of ±55 ° during simultaneous horizontal and vertical correction.		
Installation	Horizontal/vertical, free 360-degree installation		
Terminals	SDI 1 IN	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-A), Dual-link 3G-SDI (Link 1)	
	SDI 2 IN	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-B), Dual-link 3G-SDI (Link 2)	
	HDMI IN	HDMI 19-pin × 1 (Deep Color, compatible with HDCP)	
	DVI-D IN	DVI-D 24-pin × 1 (DVI 1.0 compliant, compatible with HDCP)	
	RGB 1 IN	RGB × 1 (BNC × 5): RGB/YPbPr/YCbCr/YC/VIDEO	
	RGB 2 IN	D-sub HD 15-pin (female) × 1: RGB/YPbPr	
	SYNC 1 IN/OUT / MULTI PROJECTOR SYNC IN	BNC × 1	
	SYNC 2 OUT / MULTI PROJECTOR SYNC OUT	BNC × 1	
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)	
	SERIAL OUT	D-sub 9-pin (male) × 1 for link control	
	REMOTE 1 IN / OUT	M3 × 1 for wired remote control, link control	
	REMOTE 2 IN	D-sub 9-pin (female) × 1 for external control (parallel)	
	LAN/DIGITAL LINK	RJ-45 × 1 for network, DIGITAL LINK connection, 100Base-TX, compatible with Art-Net, PjLink™ (class 1), Deep Color, HDCP	
	DC OUT	USB Type A × 2 for power supply (DC 5 V, max 900 mA)	
	Cabinet materials	Metal (Partly molded plastic)	
	Dimensions (W × H × D)	706 mm x 420 mm x 1,290 mm (27 25/32" x 16 17/32" x 50 25/32") (with protrusion parts)	
	Weight*7	Approx. 79 kg (174 lbs.)	
Operation noise*2	TBD		
Operating environment	Operating temperature: 0–45 °C (32–113 °F)*8, operating humidity: 10–80 % (no condensation) (TBD)		
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro (ET-UK20 Upgrade Kit), Smart PJ Control		

*1 Refresh-rate varies depending on vertical scanning frequency. *2 Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. *3 Operation in High Mode may reduce maintenance timing in comparison to use in Normal Mode.

*4 Only compatible with dot clock frequency of 27 MHz (pixel repetition signal). *5 WUXGA resolution is supported only when the signals are compliant with VESA CVT-RB (Coordinated Video Timing-Reduced Blanking). *6 Optical axis shift is not supported on the ET-D75LE50.

*7 Average value. May differ depending on the actual unit. *8 When projector is operating at high altitude (1,400–2,700 m) [4,593–8,858 ft], operating temperature is 0–40 °C (32–104 °F). Light source brightness may decrease depending on operating temperature. When projector is operating at high temperature or at high altitude, brightness will decrease correspondingly.

Optional Accessories

- **Fixed-Focus Lens**
ET-D75LE50 / ET-D75LE95
- **Replacement Filter Unit**
ET-EMF330
- **Geometry Manager Pro Software Upgrade Kit**
ET-UK20 Series
- **DIGITAL LINK Switcher**
ET-YFB200G
- **Zoom Lens**
ET-D75LE6 / ET-D75LE10
ET-D75LE20 / ET-D75LE30
ET-D75LE40 / ET-D75LE8
- **Smoke Cut Filter**
ET-SFR330
- **Early Warning Software**
ET-SWA100 Series
- **Digital Interface Box**
ET-YFB100G

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. The PjLink trademark is an application trademark in Japan, the United States, and other countries and regions or registered trademarks. All other trademarks are the property of their respective trademark owners. © 2016 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Website – panasonic.net/avc/projector
Facebook – www.facebook.com/panasonicprojector
YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of June 2016.

PT-RZ31KPRE2 Printed in Japan.